

SQL LOADER .

=====

1ST MAKE A FLAT TABLE NAME **name.txt**, LIKE.....

=====

1,nayan
2,robin
3,abc

=====

MAKE SQL LOADER CONTROL FILE LIKE.....

=====

control file name is "**LOAD.CTL**"

load data
infile 'g:\name.txt'
into table load_test
fields terminated by ','
(id,name)

=====

NOW LOAD THE DATA WITH THIS COMMAND

=====

C:\>SQLLDR USERID=SCOTT/TIGER CONTROL=LOAD.CTL

=====

FINALLY VIEW THE LOAD_TEST TABLE

=====

SQL> select * from load_test;

ID NAME

1 nayan
2 robin
3 abc

3 rows selected.

NOTE: **THIS IS VERY BASIC COMMAND FOR SQL LOADER**
THERE ARE A LOT OF OTHER OPTIONS WITH SQL LOADER.

Prepared by

Liakat hossain Nayan

MCP.OCAAD9i,OCA10g AS,OCPDBA8i,OCPDBA9i,OCPDBA10g,OCPDBA11g.

Email :- dba_nayan1@yahoo.com , nayan@oraclebd.com ,web:- www.oraclebd.com

“NEVER UNDERESTIMATE A HEART OF CHAMPION”

